



B2236dw

Small. Easy to use. Great value.

Compact, connected, and affordable, the high-performance Lexmark B2236dw features monochrome output up to 34 pages per minute* plus two-sided printing. Standard Wi-Fi offers enhanced connectivity and support for mobile users, while a 1-GHz processor and 256 MB of memory ensures solid performance and Lexmark full-spectrum security helps to protect sensitive information.



B2236dw



Get more done

- ▶ Get up to 34-page-per-minute* printing.
- ▶ Tackle your printing workload with the power of a 1-GHz processor and 256 MB of memory.
- ▶ Unison™ Toner replacement cartridges deliver up to 6,000 pages** of high-quality printing.
- ▶ Load and print up to 250 pages without refilling, or manual-feed single sheets.
- ▶ Use media sizes from A6 to legal in the paper tray, plus smaller media and envelopes in the manual feeder.

The right fit

- ▶ Compact dimensions of only 35.5 cm wide x 33.3 cm deep x 21.5 cm tall helps it fit almost anywhere.
- ▶ Standard Wi-Fi supports desktop and mobile devices, and complements the printer's ethernet and USB connections.
- ▶ The two-line LCD lets you configure, interact and monitor vital system information.

Robust, built-in security

- ▶ Lexmark's full-spectrum security architecture helps keep your information safe—on the document, the device, over the network, and everywhere in between.
- ▶ A range of embedded features harden device against attacks.

Built for planet earth

- ▶ Energy management features reduce power consumption in active use or sleep mode.
- ▶ Standard two-sided printing saves paper.
- ▶ Recycle cartridges through the award-winning Lexmark Cartridge Collection Programme (LCCP).

*Print and copy speeds measured in accordance with ISO/IEC 24734 and ISO/IEC 24735 respectively (ESAT). For more information see: www.lexmark.com/ISOspeeds.

** Average continuous mono declared yield in one-sided (simplex) mode up to this number of pages in accordance with ISO/IEC 19752. Actual yield will vary considerably based upon many factors. See www.lexmark.com/yields for more information.

Product specifications	Lexmark B2236dw
------------------------	-----------------

Print	
Display	2-line All Points Addressable (APA) monochrome LCD display
Print Speed: Up to ⁶	Black: 34 ppm
Time to First Page: As fast as	Black: 7.9 seconds
Print Resolution	Black: 1200 Image Quality, 2400 Image Quality, 300 x 300 dpi, 600 x 600 dpi
Memory	Standard: 256 MB / Maximum: 256 MB
Hard Disk	Not Available
Recommended Monthly Page Volume ²	250 - 2500 pages
Maximum Monthly Duty Cycle: Up to ³	30000 pages per month
Supplies ⁷	
Laser Cartridge Yields (up to) ¹	3,000-page High Yield Cartridge, 6,000-page Extra High Yield Cartridge, 1,200-page Cartridge
Imaging Unit Estimated Yield: Up to	12000 pages, based on 3 average letter/A4-size pages per print job and ~ 5% coverage
Cartridge(s) Shipping with Product ¹	700-page Black Starter Return Program Toner Cartridges
Paper Handling	
Included Paper Handling	250-Sheet Input, 150-Sheet Output Bin, Integrated Duplex, Single-Sheet Manual Feed
Paper Input Capacity: Up to	Standard: 251 pages 75 gsm bond / Maximum: 251 pages 75 gsm bond
Paper Output Capacity: Up to	Standard: 150 pages 75 gsm bond / Maximum: 150 pages 75 gsm bond
Media Types Supported	Card Stock, Envelopes, Paper Labels, Plain Paper, Refer to the Paper & Specialty Media Guide
Media Sizes Supported	10 Envelope, 7 3/4 Envelope, 9 Envelope, A4, A5, B5 Envelope, C5 Envelope, DL Envelope, Executive, Folio, JIS-B5, Legal, Letter, Statement, Universal, Oficio, A6
General Information ⁴	
Standard Ports	Ethernet 10/100BaseTX (RJ-45), USB 2.0 Specification Hi-Speed Certified (Type B), 802.11b/g/n Wireless
Noise Level: Operating	Print: 53 dBA
Specified Operating Environment	Humidity: 15 to 80% Relative Humidity, Temperature: 10 to 32°C (50 to 90°F), Altitude: 0 - 2896 Meters (9,500 Feet)
Product Warranty	1 Year Onsite Repair, 3-5 Business Day Ground Shipment
Size (mm - H x W x D) / Weight	215 x 355 x 333 mm / 6.8 kg

All information in this brochure is subject to change without notice. Lexmark is not liable for any errors or omissions.

¹Average standard page yield value declared in accordance with ISO/IEC 19752. ²"Recommended Monthly Page Volume" is a range of pages that helps customers evaluate Lexmark's product offerings based on the average number of pages customers plan to print on the device each month. Lexmark recommends that the number of pages per month be within the stated range for optimum device performance, based on factors including: supplies replacement intervals, paper loading intervals, speed, and typical customer usage. ³"Maximum Monthly Duty Cycle" is defined as the maximum number of pages a device could deliver in a month using a multishift operation. This metric provides a comparison of robustness in relation to other Lexmark printers and MFPs. ⁴Printers are sold subject to certain license/agreement conditions. See www.lexmark.com/printerlicense for details. ⁵Actual Yield may vary based on other factors such as device speed, paper size and feed orientation, toner coverage, tray source, percentage of black-only printing and average print job complexity. ⁶Print and copy speeds measured in accordance with ISO/IEC 24734 and ISO/IEC 24735 respectively (ESAT). For more information see: www.lexmark.com/ISOspeeds. ⁷Product functions only with replacement cartridges designed for use in a specific geographical region. See www.lexmark.com/regions for more details.

© 2019 Lexmark. All rights reserved.

Lexmark, the Lexmark logo and Unison are trademarks of Lexmark International, Inc., registered in the United States and/or other countries. AirPrint and the AirPrint Logo are trademarks of Apple, Inc. ENERGY STAR® is a U.S. registered mark. Google Cloud Print™ is a trademark of Google, Inc. MOPRIA®, the Mopria®Logo™ and the Mopria®Alliance logos are trademarks, service marks, and certification marks of Mopria Alliance, Inc. in the United States and other countries. All other trademarks are the property of their respective owners.

This product includes software developed by the OpenSSL Project for use in the Open SSL Toolkit (<http://www.openssl.org/>).